Type TM48-S

Premium sauna heater thermos tm48-s - Ewald Lang

The exclusive premium sauna heater line thermos Superior from Ewald Lang combines the attributes of **Design and power** like no other sauna heater model.

As high-performance electric sauna heaters with a timeless, slim design body, thermos heaters are perfect for modern Finnish home or business saunas.

especially in sauna cabins with large glass surfaces, the Lang electric heater functions as a timeless eye-catcher - thanks to its practical, **narrow footprint** it is suitable for both small private saunas (from 5 m³) and medium-sized professional cabins (up to 24 m³). The four visible sides allow free placement in the room - even as a centerpiece.

The Superior models are available in **Metallic** Design in anthracite, stainless steel and white unique in the entire sauna sector. In addition, the front side has been given a stainless steel**Application strip**which adds an eye-catching contrast to the unique look. The front strip can be individually provided with advertising labels or similar.

Ewald Lang's tried and tested thermos-Superior sauna heaters are particularly impressive due to their extremely short heating-up time and very quiet heating-up. This results in a very **environmentally friendly** and **economical** operation.

Optional equipment - thermos-S sauna heaters can be expanded in many ways:

- Granite grid support in stainless steel: sawn granite strips (4 pieces) placed above the stone basket with a fracture-rough surface
- Stove railing made of wood all 4 sides are possible, bracket angles made of stainless steel
- Cable cover in chrome steel

technical data - sauna heater tm48-s by Ewald Lang

thermos - type tm 48-S
48 x 38 x 82 cm
Stainless steel - polished anthracite metallic glaze white gloss glaze
Stainless steel - brushed or Anthracite Metallic
Stainless steel, without contact to radiators
Stainless steel
Stainless steel
Stainless steel with integrated drip protection
integrated, electrical connection screwed downwards
1500 watt, especially long-lasting
6,0 7,5 9,0 kW - 1 circuit
10,5 12,0 15,0 kW - 2 circuits
400V 3n AC
min. 7 cm (up to 10,5 kW), min. 10 cm (from 12,0 kW) on all sides to combustible parts
approx. 35 kg
approx. 30 kg
4 S S S S III 1 6 1 4 n a